

WAAS CH 78310 W35A	APP CRS 343°	Rwy Idg 5000 TDZE 35 Apt Elev 37
--	------------------------	---

RNAV (GPS) RWY 35
WASHINGTON-WARREN(OCW)

RNP APCH-GPS.

▼ Baro-VNAV and VDP NA when using Greenville altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. Rwy 35 helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Greenville altimeter setting: increase LPV DA to 401 feet, and LNAV/VNAV DA to 535 feet; increase all MDAs 60 feet and visibility LNAV Cat C/D ⅛ SM. Straight-in Minimums NA at night. Circling Rwy 17 NA at night.

MISSED APPROACH:
Climb to 2600 direct
ZIPDA and via 070°
track to HALAX
and hold.

AWOS-3 120.175	CHERRY POINT APP CON 119.35 377.175	UNICOM 122.7 (CTAF) 0
--------------------------	---	--




Figure 1: Example of a 4-segment RNAV approach. The diagram shows a 4-segment RNAV approach for RW35. The segments are labeled A, B, C, and D. Segment A is 1.3 NM, Segment B is 3.4 NM, Segment C is 6.1 NM, and Segment D is 2.4 NM. The approach is for RW35, with a 343° turn at the end of Segment C. The diagram also shows the 5000 X 100 and 5000 X 75 obstacle clearance areas. The approach is for RW35, with a 343° turn at the end of Segment C. The diagram also shows the 5000 X 100 and 5000 X 75 obstacle clearance areas.