

WAAS CH 65809 W01A	APP CRS 009°	Rwy Idg TDZE 588 Apt Elev 588
--	------------------------	---

RNAV (GPS) RWY 1
LEBANON MUNI (M54)


RNP APCH - GPS.

NA


For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16° C or above 54° C. Baro-VNAV and VDP NA when using XNX altimeter setting. Rwy 1 helicopter visibility reduction below 3/4 SM NA. Circling NA to Rwys 4 and 22. When local altimeter setting not received, use XNX altimeter setting: increase LPV DA to 1121 feet and all visibilities 1/2 SM; increase LNAV/VNAV DA to 1433 feet; increase all MDAs 40 feet and Circling Cat C visibility 1/2 SM.

MISSED APPROACH:
Climb to 3000 direct LATGE and hold.

AWOS-3 118.325	NASHVILLE APP CON 118.4 360.7	UNICOM 122.725 (CTAF)
--------------------------	---	---------------------------------



4 NM Holding Pattern JOGUB					VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 21).		3000	LATGE
GP 3.00° TCH 45					3.1 NM		3 NM	2.2 NM
009°					0.5 NM		2.5	
CATEGORY	A	B	C	D				
LPV DA	1088-1 3/8 500 (500-1 3/8)							
LNAV/VNAV DA	1400-2 1/2 812 (900-2 1/2)							
LNAV MDA	1400-1 812 (900-1)	1400-1 1/4 812 (900-1 1/4)	1400-2 1/2 812 (900-2 1/2)	1520-3 932 (1000-3)				
CIRCLING	1400-1 1/4 812 (900-1 1/4)	1440-2 1/2 852 (900-2 1/2)	1520-3 932 (1000-3)					



SE-1, 22 JAN 2026 to 19 FEB 2026

SE-1, 22 JAN 2026 to 19 FEB 2026