

VORTAC RIC	APP CRS	Rwy Ldg	5402
114.1	165°	TDZE	207
Chan 88		Apt Elev	207

VOR RWY 16


HANOVER COUNTY MUNI (OFP)

⚠

When local altimeter setting not received, use Richmond Intl altimeter setting and increase all MDA 40 feet. Rwy 16 helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH: Climbing left turn to 2000 via RIC R-345 to ANNAS INT/19 DME and hold.

ASOS 119.025	POTOMAC APP CON (001°-185°) 126.4 307.2 (186°-360°) 126.75 307.2	CLNC DEL 125.4	UNICOM 122.7 (CTAF) 0
-----------------	--	-------------------	--------------------------



VGS1 and descent angles not coincident (VGS1 Angle 3.00/TCH 40).				
Remain within 10 NM				
ANNAS INT RIC 19				
2000 345° 165° 1900 1000 1000 2.7 NM 2.3 NM				
BICAT 16.3 RIC 14				
CATEGORY	A	B	C	D
S-16	1000-1 793 (800-1)	1000-1¼ 793 (800-1¼)	1000-2¼ 793 (800-2¼)	1000-2½ 793 (800-2½)
CIRCLING	1000-1 793 (800-1)	1000-1¼ 793 (800-1¼)	1000-2¼ 793 (800-2¼)	1020-2¾ 813 (900-2¾)
BICAT FIX MINIMUMS (DME REQUIRED)				
S-16	820-1	613 (700-1)	820-1¾	613 (700-1¾)
CIRCLING	820-1	613 (700-1)	900-2 693 (700-2)	1020-2¾ 813 (900-2¾)

