

APP CRS
280°

Rwyt Ldg
TDZE
Apt Elev

3803
422
424

RNAV (GPS) RWY 28
WILLIAMSON/SODUS (SDC)

RNP APCH - GPS.

Procedure NA at night. Rwy 28 helicopter visibility reduction below 1 SM NA. When local altimeter setting not received, use Rochester altimeter setting and increase all MDAs 80 feet and LNAV visibility Cat C ¼ SM, and Circling visibility Cat C ¼ SM.

MISSED APPROACH:
Climb to 3000 direct GOYER and hold.

AWOS-3
124.2

ROCHESTER APP CON
119.55 269.6

UNICOM
122.8 (CTAF) 0

The main enroute chart displays the following details:

- MISTY 3 MOA** and **R-5203** boundaries.
- Waypoints and Altitudes:**
 - GOYER: 100°/280°, 4 NM.
 - ZIKEM: 3100 ft, 191°/101°.
 - JORAX: 3200 ft, 101°/011°.
 - WALCO: 3100 ft, 191°/295°.
- Distances:** 30 NM to ZIKEM, 20 NM to JORAX, 30 NM to WALCO.
- Altitudes:** 3100, 3200, 3400, 3700 ft.
- Angles:** 101°, 191°, 281°, 280°, 100°.
- Other:** RW28, JAKRR, (FAF), (IF/IAF), HOLD 6000/3100.

ELEV 424 TDZE 422

3000 GOYER

280°

28°

3803 X 60

4 NM Holding Pattern

WALCO

JAKRR

RW28

280°

281°

101°

6000 3100

4.5 NM

6 NM

CATEGORY	A	B	C	D
LNAV MDA	980-1	558 (600-1)	980-1½ 558 (600-1½)	NA
CIRCLING	1000-1 576 (600-1)	1020-1 596 (600-1)	1120-2 696 (700-2)	NA

MIRL Rwy 10-28 0

REIL Rwy 10 and 28 0

WILLIAMSON/SODUS, NEW YORK

Amdt 2B 06OCT22

43°14'N-77°07'W

WILLIAMSON/SODUS (SDC)

RNAV (GPS) RWY 28