

WAAS CH 42830 W21A	APP CRS 213°	Rwy Ldg TDZE 1007 Apt Elev 1019
--	------------------------	---

RNAV (GPS) RWY 21

MOUNT STERLING/MONTGOMERY COUNTY (IOB)

RNP APCH - GPS


▼

NA

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. When local altimeter setting not received, use Lexington altimeter setting and increase LPV DA to 1332 feet and all visibilities ¼ SM. Increase LNAV/VNAV DA to 1555 feet and all visibilities ¼ SM. Increase all MDAs 80 feet and LNAV visibility Cat C/D ½ SM, and Circling visibility Cat C/D ¼ SM. Baro-VNAV and VDP NA when using Lexington altimeter setting. Rwy 21 helicopter visibility reduction below ¼ SM NA.

MISSED APPROACH:
Climb to 3000 direct COXIT and hold.

AWOS-3 120.675	LEXINGTON APP CON 120.15 259.3	GCO 121.72	CTAF 122.8
--------------------------	--	----------------------	----------------------



ELEV 1019

TDZE 1007

3000

COXIT

*LNAV only.

XOEWE 2.3 NM to RW21

ISFUR 2600

RW21

1760*

2600

3000

FELPO

4 NM Holding Pattern

GP 3.00° TCH 57

CATEGORY	A	B	C	D
LPV DA	1257-¾	250 (300-¾)		
LNAV/VNAV DA	1480-1½	473 (500-1½)		
LNAV MDA	1460-1	453 (500-1)	1460-1½	453 (500-1½)
CIRCLING	1540-1 521 (600-1)	1560-1 541 (600-1)	1740-2 721 (800-2)	1740-2¼ 721 (800-2¼)