

WAAS CH 69339 W03A	APP CRS 038°	Rwy Idg TDZE 156 Apt Elev 160
--	------------------------	---

RNAV (GPS) RWY 3

WILSON INDUSTRIAL AIR CENTER (W03)


RNP APCH.

Baro-VNAV NA when using Rocky Mount altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C.

Obtain local altimeter setting on CTAF; when not received, use Rocky Mount altimeter setting: increase LPV DA to 421 and visibility all Cats ½ SM; increase LNAV/VNAV DA to 439; increase all MDA 20 feet and LNAV visibility Cats C and D ½ SM. Circling Rwy 9, 15, 27, 33 NA at night.

MISSED APPROACH: Climb to 700, then climbing left turn to 2500 direct FEBEL and hold.

WASHINGTON CENTER 123.85 279.65	UNICOM 123.0 (CTAF) 0
---	---------------------------------



ELEV 160		TDZE 156		
4 NM Holding Pattern OKTOE FALMI UVUXE 2.4 NM to RW03 RW03 GP 3.00° TCH 40 6000 ← 218° 2000 → 038° 1800 1800 960 5.9 NM 2.6 NM 2.4 NM 700 2500 FEBEL *LNAV only.				
CATEGORY	A	B	C	D
LPV DA	406-¾ 250 (300-¾)			
LNAV/VNAV DA	424-⅞ 268 (300-⅞)			
LNAV MDA	520-1 364 (400-1)	520-1¾ 364 (400-1¾)	520-2 364 (400-2)	
CIRCLING	660-1 500 (500-1)	780-1¾ 620 (700-1¾)	780-2 620 (700-2)	

REIL Rwy 3 and 21
MIRL Rwy 3-21