

WAAS
CH **99334**
W04A

APP CRS
038°

Rwy Idg
TDZE **1376**
Apt Elev **1379**

RNAV (GPS) RWY 4

EL DORADO/CAPT JACK THOMAS MEML (EQA)

⚠

NA


For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C (2°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Colonel James Jabara altimeter setting and increase all DA 51 feet and all MDA 60 feet. Baro-VNAV NA when using Colonel James Jabara altimeter setting.

MISSED APPROACH: Climb to 3100 direct SMALE and hold.

AWOS-3P
120.875

WICHITA APP CON
134.8 269.1

UNICOM
122.8 (CTAF) 0



4 NM Holding Pattern

CERVK

JIKAK

3000

3100 SMALE

*LNAV only

WINUS
1.4 NM to RW04

RW04

*1860

GP 3.00°
TCH 40

4.8 NM

3.6 NM

1.4 NM

CATEGORY	A	B	C	D
LPV DA	1576-1	200 (200-1)	NA	
LNAV/VNAV DA	1626-1	250 (300-1)	NA	
LNAV MDA	1740-1	364 (400-1)	NA	
CIRCLING	1820-1 441 (500-1)	1960-1 581 (600-1)	NA	

51

33

220° X 75

4200 X 75

038° to RW04

HIRL Rwy 4-22 and 15-33 0