

WAAS CH 40218 W36A	APP CRS 360°	Rwy Ldg 5001 TDZE 1003 Apt Elev 1003
--	------------------------	---

RNAV (GPS) RWY 36
CENTRAL KENTUCKY RGNL (RGA)



TA

For uncompensated baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Lexington altimeter setting and increase LPV DA to 1331 feet, LNAV/VNAV DA to 1345 feet and all MDA 80 feet; increase LPV all Cats and LNAV/VNAV all Cats visibility ¼ mile; increase LNAV Cats C and D ½ mile and Circling visibility Cat D ¼ mile. Helicopter visibility reduction below ¾ SM NA. VDP and Baro-VNAV NA when using Lexington altimeter setting.


MISSED APPROACH: Climb to 3100 direct QEFFO and hold.

AWOS-3 119.625	LEXINGTON APP CON 120.15 259.3	UNICOM 122.725 (CTAF) 0
--------------------------	--	-----------------------------------

MISSED APCH FIX



ELEV	1003		TDZE	1003
------	------	--	------	------



3100 VORTAC

4 NM Holding Pattern

VGSi and RNAV glidepath not coincident (VGSi Angle 3.00/TCH 26).

ANETT

3100

180°

360°

2600

360°

180°

2600

1.4 NM

1.2 NM

2.3 NM

6 NM

GP 3.00°

TCH 40

CATEGORY	A	B	C	D
LPV DA	1264-7/8	261 (300-7/8)		
RNAV/VNAV DA	1278-7/8	275 (300-7/8)		
RNAV MDA	1460-1	457 (500-1)	1460-1 3/8	457 (500-1 3/8)
CIRCLING	1460-1 457 (500-1)	1520-1 517 (600-1)	1520-1 1/2 517 (600-1 1/2)	1780-2 1/2 777 (800-2 1/2)