

APP CRS	Rwy Ldg	4580
355°	TDZE	1458
	Apt Elev	1468

RNAV (GPS) RWY 35


EASTLAND MUNI (ETN)

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -22°C (-7°F) or above 54°C (130°F).
DME/DME RNP-0.3 NA. When local altimeter setting not received, use Breckenridge altimeter setting: increase LNAV/VNAV DA to 1846 feet and all visibilities ½ SM; increase all MDAs 80 feet and LNAV and Circling visibility Cat C ¼ SM. Baro-VNAV NA when using Breckenridge altimeter setting. Circling Rwy 17 NA at night. Helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH:
Climb to 3600 direct JIXIM and hold.

AWOS-3PT 118.45	FORT WORTH CENTER 135.375 354.05	UNICOM 122.8 (CTAF) 0
--------------------	-------------------------------------	--------------------------



4 NM
Holding Pattern

BEFKO

BAWTO

3600

3200

3200

RW35

GP 3.00°
TCH 45°

←175°

355°→

355°

6.7 NM

5.3 NM

3600

↑

JIXIM

✦

CATEGORY	A	B	C	D
LNAV/ VNAV DA	1777-1 319 (400-1)			NA
LNAV MDA	1980-1	522 (600-1)	1980-1½ 522 (600-1½)	NA
CIRCLING	2120-1 652 (700-1)	2320-1¼ 852 (900-1¼)	2320-2½ 852 (900-2½)	NA

