


WAAS CH 40439 W01A	APP CRS 009°	Rwy Ldg TDZE Apt Elev	4000 268 293
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 1

AMBLER (AFM) (PAFM)

RNP APCH.	MISSED APPROACH: Climb to 1000 then climbing right turn to 3600 direct RONYE and hold, continue climb-in-hold to 3600. # Missed approach requires minimum climb of 210 feet per NM to 2300.
⚠ -36°C Circling NA west of Rwy 1-19. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -20°C or above 42°C.	

AWOS-3P 132.1	ANCHORAGE CENTER 119.2 263.0	KOTZEBUE RADIO 122.0	CTAF 122.7 0
-------------------------	--	--------------------------------	------------------------



VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 25).				1000	3600	RONYE
4 NM Holding Pattern				↑	↷	✦
GP 3.00° TCH 40				*2.3 NM to RW01 *LNAV only.		
6.2 NM				2.8 NM		
2.3 NM				RW01		
CATEGORY	A	B	C	D		
LPV DA#	518-1 250 (300-1)					
LPV DA	686-1⅓ 418 (400-1⅓)					
LNAV/ VNAV DA	811-1⅞ 543 (600-1⅞)					
LNAV MDA	1000-1 732 (800-1)	1000-1¼ 732 (800-1¼)	1000-1⅞ 732 (800-1⅞)			
CIRCLING	1000-1 707 (800-1)	1000-1¼ 707 (800-1¼)	1000-2 707 (800-2)	1000-2¼ 707 (800-2¼)		

ELEV 293 TDZE 268

MIRL Rwy 1-19 and 10-28

01 28

2400 X 60

1.1% Up

4000 X 25

0.5% Up

009°