

WAAS CH 65918 W31A	APP CRS 307°	Rwy Idg TDZE Apt Elev	4201 1394 1402
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 31

BARNES COUNTY MUNI (BAC)

RNP APCH - GPS.


▼

▲


Baro-VNAV NA when using Jamestown altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. When local altimeter setting not received, use Jamestown altimeter setting: increase LPV DA to 1721 feet and all visibilities ¾ SM; increase LNAV/VNAV DA to 1794 and all visibilities ¾ SM; increase all MDA 80 feet and visibility Circling Cat C ¼ SM. Circling NA to Rwy's 5, 8, 17, 23, 26, and 35. Rwy 31 helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH: Climb to 3000 direct CISING and hold.

AWOS-3 118.725	MINNEAPOLIS CENTER 124.2 270.3	UNICOM 122.8 (CTAF)
--------------------------	--	-------------------------------



ELEV 1402	TDZE 1394
------------------	------------------



3000	CISING	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 28).			
*LNAV only		LECPU	HUMIX	PIBBS	4 NM Holding Pattern
RW31		2 NM to RW31	3100	3100	3100
2040*		3100	307°	127°	3100
2 NM		3.2 NM	6 NM	GP 3.00° TCH 40	
CATEGORY	A	B	C	D	
LPV DA	1644-1		250 (300-1)	NA	
LNAV/VNAV DA	1717-1¼		323 (400-1¼)	NA	
LNAV MDA	1900-1		506 (500-1)	1900-1½ 506 (500-1½)	NA
CIRCLING	1920-1 518 (600-1)		2000-1 598 (600-1)	2020-1¾ 618 (700-1¾)	NA