

ILS or LOC RWY 27
GULF SHORES INTL/JACK EDWARDS FLD (TKA)

MISSED APPROACH:
Climb to 2000 on
heading 270° and
BFM VORTAC
R-145 to URIVY
INT/BFM 16.6 DME
and hold.

MSA NUN 25 NM
3100

116.35 BFM
Chan 110(Y)

URIVY INT
BFM 16.6

R-258

R-227

R-207

R-2908

294

56

170

380

1600

270°
(6.2)

090°

LOCALIZER 110.7
I-JKA
Chan 44

GEVBE
I-JKA 2.9

ORAXE INT
I-JKA 6.1
RADAR

160 ±

269°

089°

R-269

SAUFLEY
NUN
112.25

ALTERNATE MISSED
APCH FIX

IAF
SAUFLEY
112.25 NUN

LOXLY
SJL 29.1

PENSI
CEW 30.8

3100
125° (29.6)

3000
188°
(19.5)

2500
207°
(12.3)

WARLY INT
I-JKA 12.3

(IF)

ELEV 17 D TDZE 17

MIRL Rwy 17-35 1

HIRL Rwy 9-27 1

FAF to MAP 4.8 NM

Knots	60	90	120	150	180
Min:Sec	4:48	3:12	2:24	1:55	1:36

2000
↑
hdg 270°

BFM R-145 URIVY INT

*LOC only.

I-JKA 1.3 *I-JKA 2.4 GEVBE I-JKA 2.9 ORAXE INT I-JKA 6.1 WARLY INT I-JKA 12.3

1600 2500

1.1 NM 0.5 3.2 NM 6.2 NM

CATEGORY	A	B	C	D
S-ILS 27	217- ¹ / ₂		200 (200- ¹ / ₂)	
S-LOC 27	540- ¹ / ₂ 523 (600- ¹ / ₂)		540-1 523 (600-1)	
C CIRCLING	540-1 523 (600-1)		740-2 723 (800-2)	740-2 ¹ / ₄ 723 (800-2 ¹ / ₄)
GEVBE FIX MINIMUMS				
S-LOC 27	420- ¹ / ₂ 403 (500- ¹ / ₂)		420- ³ / ₄ 403 (500- ³ / ₄)	
C CIRCLING	480-1 463 (500-1)		740-2 723 (800-2)	740-2 ¹ / ₄ 723 (800-2 ¹ / ₄)

** 620 when using Pensacola INT altimeter setting.