

WAAS CH 42539 W22A	APP CRS 215°	Rwy Idg TDZE 5817 Apt Elev 5837
--	------------------------	---

RNAV (GPS) RWY 22

DOUBLE EAGLE II (A/E/G)

⚠



For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -26°C (-14°F) or above 46°C (114 °F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Albuquerque Intl Sunport altimeter setting and increase LPV DA to 6111, LNAV-VNAV DA to 6234, increase all MDA 100 feet, and increase LNAV/VNAV visibility all Cats and LNAV Cat C/D visibility ¾ mile and Circling Cat C/D visibility ½ mile. For inop MALSR, increase LNAV/VNAV all Cats visibility to 1 mile. For inop MALSR when using Albuquerque Intl Sunport altimeter setting, increase LPV all Cats visibility to 1 mile and LNAV/VNAV all Cats and LNAV Cat C/D visibility to 1 ¾ mile.

MALSR

AS

MISSED APPROACH:
Climb to 8800 direct
YECUG and hold.

ATIS 119.025	ALBUQUERQUE APP CON 127.4 253.5	DOUBLE EAGLE II TOWER ★ 120.15 (CTAF) 0	GND CON 121.625	CLNC DEL 124.8 (When twr closed)
------------------------	---	--	---------------------------	---



CATEGORY	A	B	C	D
LPV DA		6017-½	200 (200-½)	
LNAV/VNAV DA		6140-⅝	323 (400-⅝)	
LNAV MDA	6200-½	383 (400-½)	6200-⅝	383 (400-⅝)
CIRCLING	6400-1	563 (600-1)	6420-1½ 583 (600-1½)	6640-2½ 803 (900-2½)

