

WAAS

CH **69318**

W30A

APP CRS

296°

Rwy Idg

5650

TDZE

2131

Apt Elev

2135

RNAV (GPS) RWY 30

WATFORD CITY MUNI (S25)

RNP APCH - GPS.

VDP NA when using Williston altimeter setting. When local altimeter setting not received, use Williston Basin Int altimeter setting: increase LPV DA to 2488 feet; all visibility ¼ SM. Increase all MDAs 120 feet and LNAV visibility Cat C/D ¼ SM, and Circling visibility Cat C/D ½ SM.

MISSED APPROACH: Climb to 4500 direct GERHE and hold.

AWOS-3PT 118.125	SALT LAKE CENTER 126.85 305.2	UNICOM 122.8 (CTAF) 0
----------------------------	---	---------------------------------

MSA RW30 25 NM
4700

2862 Δ

2428 Δ

Δ 2306

RW30

2684 Δ

2851 Δ

(FAF) BOWIS

4100 296° (4.1)

(IF/IAF) CIPGO

116° 5 NM

HOLD 6000 4300

4300 NoPT 20° (11)

Δ (IAF) POVNY

MISSED APCH FIX

GERHE

5 NM 16° 296°

ELEV 2135 D TDZE 2131

Δ (IAF) HASOS

4300 NoPT 026° (14)

Δ 3492

Procedure NA for arrivals at POVNY on V71 northwest bound.

Procedure NA for arrivals at HASOS on V439 southeast bound.

4500	GERHE	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 45).				5 NM Holding Pattern
↑	Δ	BOWIS	CIPGO	116° → 6000 ← 296° 4300		GP 3.00° TCH 40
1.6 NM to RW30		4100	296°	4100		
RW30		1.6	4.5 NM	4.1 NM		
6530 X 75						
0.1, 1.1% UP						
296°						
CATEGORY		A	B	C	D	
LPV DA		2381-3 ³ / ₄		250 (300-3 ³ / ₄)		
LNAV MDA		2680-1	549 (600-1)	2680-1 ⁵ / ₈	549 (600-1 ⁵ / ₈)	
CIRCLING		2700-1 565 (600-1)	2760-1 625 (700-1)	2760-1 ³ / ₄ 625 (700-1 ³ / ₄)	2960-2 ³ / ₄ 825 (900-2 ³ / ₄)	

WATFORD CITY, NORTH DAKOTA

Amdt 1A 03NOV22

47°48'N-103°15'W

WATFORD CITY MUNI (S25)

RNAV (GPS) RWY 30