

LOC I-PBV	APP CRS	Rwy Idg	4982
110.1	111°	TDZE	128
		Apt Elev	128

ILS or LOC RWY 11

ST GEORGE (PBV) (PAPB)

⚠

DME from SRI NDB/DME. Simultaneous reception of I-PBV and SRI DME required. Circling NA north of Rwy 11-29. ADF and DME required. Inop table does not apply to S-LOC 11 Cats A and B and S-ILS 11 all Cats.

MALSF

MISSED APPROACH: Climb to 3200 on SRI NDB/DME bearing 110° to LIJFY/SRI 7.7 DME and hold, continue climb-in-hold to 3200.

ASOS	ANCHORAGE CENTER	CTAF
135.45	119.1 339.8	122.8

ELEV 128	TDZE 128
----------	----------

111° 5 NM from FAF

REIL Rwy 29
HIRL Rwy 11-29

FAF to MAP 5 NM

Knots	60	90	120	150	180
Min:Sec	5:00	3:20	2:30	2:00	1:40

ADF and DME REQUIRED

Remain within 10 NM	APOTE SRI 6	3200	LIJFY SRI 7.7	
3000	2100	WVOG SRI 3.3	*LOC only	
291°	111°	*SRI 2.7	SRI 1	
2100	*1060	SRI NDB/DME		
GS 3.60° TCH 56	2.7 NM	0.6 NM	1.7 NM	
CATEGORY	A	B	C	D
S-ILS 11	428-1	300 (300-1)		NA
S-LOC 11	840-1	712 (800-1)	840-1¾ 712 (800-1¾)	NA
CIRCLING	840-1 712 (800-1)	980-1¼ 852 (900-1¼)	980-2½ 852 (900-2½)	NA

ST GEORGE, ALASKA
Amdt 1 13SEP18

56°35'N-169°40'W

ST GEORGE (PBV) (PAPB)
ILS or LOC RWY 11