

WAAS
CH **50401**
W18A

APP CRS
180°

Rwy Ldg **3500**
TDZE **675**
Apt Elev **675**

RNAV (GPS) RWY 18
LEWIS COUNTY RGNL (6M6)

▼

NA

Baro-VNAV NA. Use Quincy altimeter setting; when not received use Kirksville altimeter setting:
increase LPV DA to 1098 feet; increase LNAV/VNAV DA to 1145 feet; increase all MDA 80 feet.

MISSED APPROACH:

Climb to 2300 direct
GRITE and hold.

UIN ASOS 121.425	KANSAS CITY CENTER 126.225 317.775	UNICOM 122.7 (CTAF) 0
----------------------------	--	---------------------------------

The main chart displays the RNAV (GPS) RWY 18 approach. Key features include:

- Initial Approach:** A 5 NM hold at 6000/2500, followed by a 180° turn to 2300 (5:1) and a 360° turn to 2500 NoPT (5).
- Intermediate Approach:** A 270° turn to 2300 (5:1) and a 180° turn to 2300.
- Final Approach:** A 180° turn to 2300, followed by a 360° turn to 2300 and a 180° turn to 2300.
- Altitudes:** 2300, 2500, 2700, 3000, 3500, 3600, 3700, 3800, 3900, 4000, 4100, 4200, 4300, 4400, 4500, 4600, 4700, 4800, 4900, 5000, 5100, 5200, 5300, 5400, 5500, 5600, 5700, 5800, 5900, 6000, 6100, 6200, 6300, 6400, 6500, 6600, 6700, 6800, 6900, 7000, 7100, 7200, 7300, 7400, 7500, 7600, 7700, 7800, 7900, 8000, 8100, 8200, 8300, 8400, 8500, 8600, 8700, 8800, 8900, 9000, 9100, 9200, 9300, 9400, 9500, 9600, 9700, 9800, 9900, 10000.
- Navigation Aids:** WOLER, VEJTY, YUKON, GRITE, and RW18.
- Obstacles:** 1643 M, 857 M, 796 M.

ELEV 675

TDZE 675

81

180°

0.3% UP

3500 X 60

36

2300

GRITE

YUKON

2300

GLOBE

2300

RW18

2300

4.9 NM

5.1 NM

4 NM Holding Pattern

360° → 6000

← 180° 2500

GP 3.00°

TCH 40

CATEGORY	A	B	C	D
LPV DA	1035-1¼	360 (400-1¼)	NA	NA
LNAV/VNAV DA	1082-1½	407 (500-1½)	NA	NA
LNAV MDA	1220-1	545 (600-1)	NA	NA

MONTICELLO, MISSOURI

LEWIS COUNTY RGNL (6M6)

Orig-D 05DEC19

40°08'N-91°41'W

RNAV (GPS) RWY 18