

WAAS CH 62934 W35A	APP CRS 356°	Rwy Ldg TDZE Apt Elev	4200 1320 1325
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 35

SCRIBNER STATE (SCB)

RNP APCH - GPS.

▼

▲

NA

Baro-VNAV NA. Circling Rwy 17 NA at night. Use FET altimeter setting; when not received, use AHQ altimeter setting and increase LPV DA to 1629 feet; increase LNAV/VNAV DA to 1767 feet and all visibilities 1/8 SM. Increase all MDAs 40 feet.

FET AWOS-3
121.275

OMAHA APP CON
135.875 354.05

CTAF
122.9

30 NM to GUDGE

3600

GUDGE

086°

266°

GUDGE

086°

266°

15 NM to GUDGE

3600

30 NM to GUDGE (NoPT)

3800

1515

RW35

ZIDMA

2.4 NM to RW35

(FAF) FENIG

2900

356°

(4.8)

(IF/IAF) GUDGE

356°

4 NM

HOLD

6000

3600

MISSED APCH FIX

4 NM

176°

356°

AXODE

3300

AXODE

RW35

ZIDMA

2.4 NM to RW35

FENIG

2900

GUDGE

4 NM Holding Pattern

176°

356°

6000

3600

GP 3.00°

TCH 40

2.4 NM

2.4 NM

4.8 NM

2120

2900

CATEGORY	A	B	C	D
LPV DA	1606-7/8	286 (300-7/8)		NA
LNAV/VNAV DA	1744-1 1/4	424 (500-1 1/4)		NA
LNAV MDA	1840-1	520 (600-1)		NA
CIRCLING	1900-1	575 (600-1)		NA

ELEV 1325

TDZE 1320

4200 X 75

35

356°

MIRL Rwy 17-35

SCRIBNER, NEBRASKA
Amdt 1C 07AUG25

41°37'N-96°38'W

SCRIBNER STATE (SCB)

RNAV (GPS) RWY 35

NC-2, 22 JAN 2026 to 19 FEB 2026

NC-2, 22 JAN 2026 to 19 FEB 2026