


WAAS CH 58041 W11A	APP CRS 111°	Rwy Idg 3200 TDZE 29 Apt Elev 29
--	------------------------	---

RNAV (GPS) RWY 11

BUCKLAND (BVK)(PABL)

RNP APCH.	MISSED APPROACH: Climb to 3100 direct JAMUR and hold, continue climb-in-hold to 3100.
▼ Baro-VNAV and VDP NA when using Selawik altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -21°C or above 54°C. ▲ When local altimeter setting is not received use Selawik altimeter setting: increase DA to 387 feet and all visibilities $\frac{3}{8}$ SM; increase all MDAs 120 feet and visibility Cat C $\frac{1}{4}$ SM.	

AWOS-3P 135.15	ANCHORAGE CENTER 119.2 263.0	KOTZEBUE RADIO 122.3	CTAF 122.9 0
--------------------------	--	--------------------------------	------------------------



ELEV 29		TDZE 29	
4 NM Holding Pattern		JAMUR	
6000 ← 290°		3100	
2900 → 110°		* LNAV only.	
GP 3.00°		* 0.9 NM to RWY 11	
TCH 30		RWY 11	
7.7 NM		3.9 NM	
1 NM		0.9	
CATEGORY	A	B	D
LPV DA	279-1	250 (300-1)	NA
LNAV/VNAV DA	279-1	250 (300-1)	NA
LNAV MDA	340-1	311 (400-1)	NA
CIRCLING	540-1	511 (600-1)	NA
		640-1 $\frac{3}{4}$	
		611 (700-1 $\frac{3}{4}$)	
MRL Rwy 11-29 0			