

RNAV (GPS) RWY 19
BEECH RIVER RGNL (PVE)

T For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5 °F) or above 54 °C (130°F). A DME/DME RNP-0.3 NA. When local altimeter setting not received, use Jackson altimeter setting: increase LPV all Cats DA to 828 and all Cats visibility ¼ mile; increase LNAV/VNAV all Cats DA to 890 and all Cats visibility ¾ mile; increase all MDA 100 feet and LNAV Cats C/D and Circling Cat C visibility ¼ mile and Circling Cat D visibility ½ mile. VDP and Baro-VNAV NA when using Jackson altimeter setting.	MISSED APPROACH: Climb to 3000 direct COCTA and hold.
--	---

3000 COCTA

VGS and RNAV glidepath not coincident (VGS Angle 3.29/TCH 30).

4 NM Holding Pattern

*1380

*2200

1.2 NM

1.5 NM

2.6 NM

6 NM

193°

013°

193°

GP 3.00 TCH 40

CATEGORY	A	B	C	D
LPV DA	738-7 $\frac{7}{8}$		250 (300-7 $\frac{7}{8}$)	
LNAPV/VNAV DA	800-1		312 (400-1)	
LNAPV MDA	940-1	452 (500-1)	940-1 $\frac{3}{8}$	452 (500-1 $\frac{3}{8}$)
CIRCLING	940-1 452 (500-1)	980-1 492 (500-1)	1000-1 $\frac{1}{2}$ 512 (600-1 $\frac{1}{2}$)	1200-2 $\frac{1}{4}$ 712 (800-2 $\frac{1}{4}$)

SE-1, 22 JAN 2026 to 19 FEB 2026