


(ALTNN2. ALTNN) 24081

Al-10263 (FAA)

## ALTN TWO DEPARTURE (RNAV)

FAA)  
MIAMI HOMESTEAD GENERAL AVIATION (X51)  
HOMESTEAD, FLORIDA

MIAMI DEP CON 125.5 354.1 AWOS-3 118.375	RNAV 1 - DME/DME/IRU or GPS. RADAR required.		<b>TOP ALTITUDE: ASSIGNED BY ATC</b>
---	---	---	--



## TAKEOFF MINIMUMS

Rwy 10: Standard with minimum climb of 500'/NM to 2400.

Rwy 18: Standard with minimum climb of 500'/NM to 1800.

Rwy 28: Standard with minimum climb of 500'/NM to 1900.

Rwy 36: Standard with minimum climb of 500'/NM to 2200.

NOTE: Chart not to scale.

T

## DEPARTURE ROUTE DESCRIPTION

**TAKEOFF RUNWAY 10:** Climb on heading 096° or as assigned by ATC for RADAR vectors to cross AGERS at or above 5000, thence. . . .

**TAKEOFF RUNWAY 18:** Climb on heading 185° or as assigned by ATC for RADAR vectors to cross AGERS at or above 5000, thence. . . .

**TAKEOFF RUNWAY 28:** Climb on heading 276° or as assigned by ATC for RADAR vectors to cross AGERS at or above 5000, thence. . . .

**TAKEOFF RUNWAY 36:** Climb on heading 005° or as assigned by ATC for RADAR vectors to cross AGERS at or above 5000, thence. . . .

.... on track 360° to PERTS, then on track 357° to ALTN, then on assigned transition, maintain ATC assigned altitude, expect filed altitude within 10 minutes after departure.

## DUCEN TRANSITION (ALTNN2.DUCEN)

ALTN TWO DEPARTURE(RNAV)  
(ALTN2 ALTN) 21MAR24

HOMESTEAD, FLORIDA