

APP CRS
011°

Rwy Ldg **5000**
TDZE **65**
Apt Elev **65**

RNAV (GPS) RWY 1

INVERNESS (INF)

▼

⚠

Rwy 1 helicopter visibility reduction below 1 SM NA. Procedure NA at night. When local altimeter setting not received, use OCF altimeter setting and increase all MDAs 60 feet and LNAV visibility Cat C ½ SM, and Circling visibility Cat C ¼ SM.

MISSED APPROACH: Climb to 2000 direct GIOVA and on track 050° to VANNI and hold.

AWOS-3 119.975	JACKSONVILLE APP CON 118.6 251.15	UNICOM 122.725 (CTAF) 0
--------------------------	---	-----------------------------------

Diagram illustrating the RNP APCH - GPS procedure for RNAV (GPS) RWY 1, INVERNESS (INF). The procedure starts at WESAS (1700 ft) and proceeds through waypoints: CUBIL (FAF), TOCOP (2.2 NM to RW01), GIOVA (13.4 NM), and VANNI (4 NM). The procedure is NA for arrivals at DADES on V581 southbound. A missed approach is shown: Climb to 2000 direct GIOVA and on track 050° to VANNI and hold.

WESAS

2000

011°

CUBIL

1700

940

5 NM

2 NM

2.2 NM

RW01

2000

GIOVA

tr 050°

VANNI

TOCOP

2.2 NM to RW01

TCH 47

CATEGORY	A	B	C	D
LNAV MDA	500-1	435 (500-1)	500-1¼ 435 (500-1¼)	NA
CIRCLING	660-1	595 (600-1)	660-1½ 595 (600-1½)	NA

ELEV 65

TDZE 65

MIRL Rwy 1-19 0

REIL Rwys 1 and 19 0

61

0.5% UP

5000 X 75

011°

INVERNESS, FLORIDA

Amdt 1 07AUG25

28°48'N-82°19'W

INVERNESS (INF)

RNAV (GPS) RWY 1