

COLT, ARKANSAS

AL-10682 (FAA)

26022

WAAS CH 53532 W36A	APP CRS 002°	Rwy Ldg 5003 TDZE 235 Apt Elev 239
--	------------------------	---

RNAV (GPS) RWY 36
DELTA RGNL (DRP)

RNP APCH - GPS.

T Baro-VNAV and VDP NA when using West Memphis altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. When local altimeter setting not received, use West Memphis altimeter setting: increase LPV DA to 503 feet and all visibilities ½ SM; increase LNAV/VNAV DA to 755 feet; increase all MDAs 80 feet.


MISSED APPROACH: Climb to 3000 direct UH1H and hold, continue climb-in-hold to 3000.

AWOS-3P
120.0

MEMPHIS CENTER
135.3 335.8

UNICOM
123.0 (CTAF) **L**

MISSED APCH FIX



RW36

551 Δ^{445}
(FAF)
ZIKJE

21000 (6.)

HOLD $\overline{6000}$
3000

ELEV 239

TDZE 235

HIRL Rwy 18-36 **L**
REIL Rwy 18 & 36 **L**

4 NM
Holding Pattern USUDY

6000 ←

3000

GP 3.00°
TCH 44

ZIKJE

2100

1.3 NM to

RW36

← 6

— 4.4 NM —

CATEGORY	A	B	C	D
LPV DA	435- ³ / ₄	200 (200- ³ / ₄)	NA	
LNAV/VNAV DA	687-1 ³ / ₈	452 (500-1 ³ / ₈)	NA	
LNAV MDA	700-1	465 (500-1)	NA	
CIRCLING	760-1	521 (600-1)	NA	

8

1

1

50

03 X

002°-

COLT, ARKANSAS

Amdt 1 11JUL24

35°07'N-90°50'W

DELTA RGNL (DRP)

RNAV (GPS) RWY 36

SC-1, 22 JAN 2026 to 19 FEB 2026

SC-1, 22 JAN 2026 to 19 FEB 2026