

WAAS CH 90537 W03A	APP CRS 032°	Rwy Ldg TDZE Apt Elev	5598 5157 5193
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 3

BLAKE FLD (AJZ)

RNP APCH.


▼

▲

Baro-VNAV NA when using Montrose altimeter setting. For uncompensated Baro-VNAV systems, procedure NA below -25°C or above 54°C. When local altimeter setting not received, use Montrose altimeter setting: increase #LPV DA to 5529 feet and visibility all Cats ¾ SM, increase LPV DA to 5670 feet and visibility all Cats ½ SM, increase LNAV/VNAV DA to 5979 feet and visibility all Cats ¼ SM. Increase all MDA 140 feet and visibility Cat B ¼ SM, Cat C ½ SM and Circling Cat A ¼ SM. VDP NA when using Montrose altimeter setting. Circling NA to Rwy 14 and 32.
Missed approach requires minimum climb of 250 feet per NM to 6900.

MISSED APPROACH: Climb to 7000 then climbing right turn to 11600 direct CAKBI and on track 187° to NADIN and hold, continue climb-in-hold to 11600.

AWOS-3 134.0	DENVER CENTER 127.1 343.65	UNICOM 122.8 (CTAF) 0
------------------------	--------------------------------------	---------------------------------



	CAKBI	BUWME	AIRNS	7000	11600	CAKBI	tr 187°	NADIN
	8900	7700	7100	7100				
	GP 3.00° TCH 38							
	3.9 NM	2.1 NM	3.9 NM	2.2 NM				
CATEGORY	A	B	C	D				
#LPV DA	5407-1	250 (300-1)		NA				
LPV DA	5548-1½	391 (400-1½)		NA				
LNAV/VNAV DA	5857-2	700 (700-2)		NA				
LNAV MDA	5840-1	683 (700-1)	5840-2 683 (700-2)	NA				
CIRCLING	5900-1 707 (800-1)	6340-1½ 1147 (1200-1½)	6680-3 1487 (1500-3)	NA				

