

APP CRS  
**038°**

Rwy Ldg  
TDZE  
**3607**

Apt Elev  
**3607**

RNAV (RNP) Z RWY 4

RICK HUSBAND AMARILLO INTL (AMA)

For uncompensated Baro-VNAV systems, procedure NA below -14°C (7°F) or above 53°C (128°F).  
RF required. GPS required. For inop ALS, increase RNP 0.30 all Cats visibility to 1½ SM.

MALSR

MISSED APPROACH: (Do not exceed 185K until MAWGO)  
Climb to 5400 on track 038° to KILTE, right turn to MAWGO, then track 157° to CAUDE and hold.

|                             |                                         |                                             |                               |                                   |                         |
|-----------------------------|-----------------------------------------|---------------------------------------------|-------------------------------|-----------------------------------|-------------------------|
| ATIS<br><b>118.85 350.3</b> | AMARILLO APP CON★<br><b>119.5 307.0</b> | AMARILLO TOWER★<br><b>118.3(CTAF) 257.9</b> | GND CON<br><b>121.9 348.6</b> | CLNC DEL<br><b>121.65 239.275</b> | UNICOM<br><b>122.95</b> |
|-----------------------------|-----------------------------------------|---------------------------------------------|-------------------------------|-----------------------------------|-------------------------|

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 61).

5400  
↑  
tr 038°

MAWGO

CAUDE

See planview for multiple IF locations.

GP 3.00°  
TCH 44

4600

038°

RW04

3 NM

|             |   |         |             |   |
|-------------|---|---------|-------------|---|
| CATEGORY    | A | B       | C           | D |
| RNP 0.12 DA |   | 3969/40 | 362 (400-¾) |   |
| RNP 0.30 DA |   | 4019/50 | 412 (500-1) |   |

**AUTHORIZATION REQUIRED**

REIL Rwy 13   
HIRL Rwy 4-22 and 13-31

ELEV 3607 TDZE 3607

AMARILLO, TEXAS  
Amdt 1 12OCT17

35°13'N-101°42'W

RICK HUSBAND AMARILLO INTL (AMA)  
RNAV (RNP) Z RWY 4