

# OZARK EIGHT DEPARTURE

ATIS 128.7 256.7  
 CLNC DEL 119.875 263.025  
 GND CON 119.2 275.8  
 SCOTT TOWER 128.25 253.5  
 ST LOUIS DEP CON 125.2 281.5

**TOP ALTITUDE:**  
**3000**

**TAKEOFF MINIMUMS**  
 Rwys 14L/R, 32R: Standard.  
 Rwy 32L: 300-1½ or standard with minimum climb  
 of 250' per NM to 800.



HALLSVILLE:  
 114.2 HLW  
 Chan 89

8000  
 \*2500  
 281°  
 (46)

8000  
 \*2100  
 281°  
 (32)

CABIT

ST. LOUIS:  
 117.4 STL  
 Chan 121

NOTE: DME and RADAR required.

**DEPARTURE ROUTE DESCRIPTION**

Climb on assigned heading for vector to appropriate route. Maintain 3000 or assigned altitude, thence . . . . .  
 . . . . . (transition). Expect filed altitude 10 minutes after departure.

**HALLSVILLE TRANSITION [OZARK8.HLV]:** From over STL VORTAC on STL R-281 to CABIT, then on STL R-281 and HLW R-095 to HLW VORTAC.

NOTE: Chart not to scale.

# OZARK EIGHT DEPARTURE