

VORTAC ELP	APP CRS	Rwy Ldg	9025
115.2	245°	TDZE	3962
Chan 99		Apt Elev	3962

VOR RWY 26L

EL PASO INTL (ELP)

⚠

ASR

Inop table does not apply to S-26L and CINAG fix minimums S-26L. Circling NA for Cat D northwest of Rwy 4-22.

MALSR

MISSED APPROACH: Climb to 4500 then climbing left turn to 7100 on heading 050° and on ELP VORTAC R-081 to FEMOL INT/9 DME and hold.

D-ATIS	EL PASO APP CON	EL PASO TOWER	GND CON	CLNC DEL
120.0 254.3	124.25 298.85	118.3 239.275	121.9 348.6	125.0 379.1

Procedure NA for arrivals at WATEX on V94-611 northwest bound.

Procedure NA for arrivals at RIOWE on V16-222 eastbound.

4500

7100

hdg 050°

ELP R-081

FEMOL INT

CATEGORY	A	B	C	D	E
S-26L	4480-1 518 (600-1)		4480-1 ³ / ₈ 518 (600-1 ³ / ₈)		NA
CIRCLING	4480-1 518 (600-1)		4480-1 ¹ / ₂ 518 (600-1 ¹ / ₂)	4680-2 718 (800-2)	NA
CINAG FIX MINIMUMS (DUAL VOR RECEIVERS OR DME REQUIRED)					
S-26L	4380-1 418 (500-1)		4380-1 ¹ / ₈ 418 (500-1 ¹ / ₈)		NA
CIRCLING	4420-1 458 (500-1)	4440-1 478 (500-1)	4480-1 ¹ / ₂ 518 (600-1 ¹ / ₂)	4680-2 ¹ / ₄ 718 (800-2 ¹ / ₄)	NA

ELEV 3962 TDZE 3962

MIRL Rwy 8L-26R
REIL Rws 4 and 8R
HIRL Rws 4-22 and 8R-26L

	FAF to MAP 3.8 NM				
Knots	60	90	120	150	180
Min:Sec	3:48	2:32	1:54	1:31	1:16

EL PASO, TEXAS

Amdt 32D 20APR23

31°48'N-106°23'W

EL PASO INTL (ELP)

VOR RWY 26L