

WAAS CH 97413 W35A	APP CRS 355°	Rwy Ldg 8002 TDZE 1147 Apt Elev 1167
--	------------------------	---

RNAV (GPS) RWY 35

ENID WOODRING RGNL (WDG)




RNP APCH-GPS.

⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. Baro-VNAV and VDP NA when using GOK altimeter setting. Circling Rwy 13 NA at night. When local altimeter setting not received, use GOK altimeter setting and increase LPV DA to 1445 feet; increase LNAV/VNAV DA to 1495 feet and all visibilities ½ SM. Increase all MDAs 100 feet and LNAV visibility Cat C/D/E ¼ SM, and Circling visibility Cat C/D ½ SM. For inop ALS, increase LPV Cat E visibility to ¾ SM, increase LNAV/VNAV all Cats visibility to ¾ SM, and increase LNAV Cat E visibility to 1 ⅜ SM.

MALSR 

MISSED APPROACH: Climb to 3000 direct NIDME and hold.

AWOS-3PT 123.725	VANCE APP CON * 121.3 346.325	WOODRING TOWER * 118.9 (CTAF) 0 257.95	GND CON 121.925
----------------------------	---	--	---------------------------



CATEGORY	A	B	C	D	E
LPV DA	1347-½		200 (200-½)		
LNAV/VNAV DA	1397-½		250 (300-½)		
LNAV MDA	1600-½	453 (500-½)	1600-7/8		453 (500-7/8)
CIRCLING	1760-1	593 (600-1)	1820-1¾ 653 (700-1¾)	1880-2¼ 713 (800-2¼)	2000-3 833 (900-3)

SC-1, 19 FEB 2026 to 19 MAR 2026

SC-1, 19 FEB 2026 to 19 MAR 2026