



APP CRS	Rwy Ldg	7913
305°	TDZE	8
	Apt Elev	9

RNAV (RNP) Y RWY 30

MIAMI INTL (MIA)

▽ ▲ NA	For inoperative MALS, increase RNP 0.23 all Cats visibility to 1½, RNP 0.30 all Cats to 1¾. GPS Required. For uncompensated Baro-VNAV systems, procedure NA below 6°C (42°F) or above 48°C (119°F).	MALS 	MISSED APPROACH: Climb to 3000 direct VEPCO and via 342° track to BRBRA and hold.

D-ATIS	MIAMI APP CON	MIAMI TOWER	GND CON
119.15	124.85 322.3	118.3 256.9	121.8 (8L/8R/12/26L/26R) 127.5 (9/27/30) 348.6



ELEV 9	D	TDZE 8			
3000	VEPCO	342° tr	BRBRA	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 71).	Procedure Turn NA
	RW30	BIRDD 1600	OLDDDE	SHANN	305° 3000
					GP 3.00° TCH 51
	4.8 NM	4.4 NM	6.1 NM		
CATEGORY	A	B	C	D	
RNP 0.23 DA		426-1¼	418 (500-1¼)		
RNP 0.30 DA		521-1½	513 (600-1½)		

AUTHORIZATION REQUIRED

SE-3, 19 FEB 2026 to 19 MAR 2026

SE-3, 19 FEB 2026 to 19 MAR 2026