

RNAV (RNP) Z RWY 35R

OKC WILL ROGERS INTL (OKC)




| | |
|------------------------|-------------------------|
| APP CRS 356° | Rwy Ldg 9802 |
| | TDZE 1294 |
| | Apt Elev 1296 |

ASR For uncompensated Baro-VNAV systems, procedure NA below -12°C (11°F) or above 54°C (130°F). GPS required. Simultaneous approach authorized with Rwy 35L. Use of FD or AP providing RNAV track guidance required during simultaneous operations.

ALSF-2

MISSED APPROACH: Climb to 5000 on track 356° to ATREC and hold, continue climb-in-hold to 5000.

| | | | |
|-------------------------|--|--------------------------------------|-------------------------------|
| D-ATIS 125.85 | OKE CITY APP CON 124.6 266.8 | ROGERS TOWER 119.35 269.45 | GND CON 121.9 348.6 |
|-------------------------|--|--------------------------------------|-------------------------------|



| | | | | |
|-------------|---|---------|-------------|---|
| CATEGORY | A | B | C | D |
| RNP 0.16 DA | | 1570/24 | 276 (300-½) | |
| RNP 0.30 DA | | 1674/39 | 380 (400-¾) | |

AUTHORIZATION REQUIRED

SC-1, 19 FEB 2026 to 19 MAR 2026

SC-1, 19 FEB 2026 to 19 MAR 2026