


LOC/DME I-PIH 110.3 Chan 40	APP CRS 211°	Rwy Ldg TDZE 9059 4452	Apt Elev 4452
---	------------------------	--	-------------------------

ILS or LOC RWY 21

POCATELLO RGNL (PIH)


DME required.	MALSR	MISSED APPROACH: Climb to 7000 direct PIH VOR/DME and on PIH R-235 to COLAY/PIH 1.5 DME and hold, do not exceed 230K in holding pattern.
<p>▼ Circling NA southeast of Rwy 3-21. For inop ALS, increase S-ILS-21</p> <p>▲ Cat E visibility to RVR 4000, S-LOC-21 Cat C/D/E to RVR 4500. *RVR 1800 authorized with use of FD or AP or HUD to DA.</p>		

ATIS 135.625	SALT LAKE CENTER 128.35 239.25	POCATELLO TOWER * 119.1 (CTAF) 257.8	GND CON 121.9	UNICOM 122.95
------------------------	--	--	-------------------------	-------------------------



ELEV 4452	D TDZE 4452
-----------	--------------------

7000	PIH	PIH	COLAY	VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 52).
↑	☐	R-235	△	
Use I-PIH DME when on the localizer course.				
I-PIH 1.6	I-PIH 2.4	I-PIH 3.3	HESNO I-PIH 6.3	CUPTA I-PIH 11.6
0.8	0.9	3	5.3	5
BARS E I-PIH 16.6				
One Minute Holding Pattern				
8900				
7800				
GS 3.00°				
TCH 56				



CATEGORY	A	B	C	D	E
S-ILS 21*		4652/24	200 (200-½)		
S-LOC 21		4760/24	308 (400-½)		
CIRCLING	4860-1 408 (500-1)	4920-1 468 (500-1)	4920-1½ 468 (500-1½)	5020-2 568 (600-2)	5060-2¼ 608 (700-2¼)

HIRL Rwy 3-21	①
MIRL Rwy 17-35	①
REIL Rws 3 and 17	①

NW-1, 19 FEB 2026 to 19 MAR 2026

NW-1, 19 FEB 2026 to 19 MAR 2026