

WAAS CH <b>58299</b> <b>W01A</b>	APP CRS <b>006°</b>	Rwy Ldg <b>6300</b> TDZE <b>6431</b> Apt Elev <b>6451</b>
--	------------------------	---

# RNAV (GPS) X RWY 1

## JACKSON HOLE (JAC)

RNP APCH-GPS.		MALS =	MISSED APPROACH: Climb to 14000 direct QUIRT and on track 088° to DNW VOR/DME and hold, continue climb-in-hold to 14000. *Missed approach requires minimum climb of 385 feet per NM to 7700.
⚠ Circling NA east of Rwy 1-19. Baro-VNAV NA. ⚠ Circling NA for Cat D. Inop table does not apply to LPV, LPV*, LNAV/VNAV, and LNAV Cat C/D. ❄ -21°C		A2	

D-ATIS <b>120.625</b>	SALT LAKE CENTER <b>133.25 285.6</b>	JACKSON TOWER* <b>118.075 (CTAF) 1</b>	GND CON <b>124.55</b>	UNICOM <b>122.95</b>
--------------------------	---	---	--------------------------	-------------------------



ELEV 6451	D	TDZE 6431
-----------	---	-----------

7 NM Holding Pattern 17500 ← 186° 11700 → 006° GP 3.00° TCH 50	HOMVA	VALCU	DECEV	ZUGEN	COVGI	QUIRT	Ir	DNW
	14000	11000	10400	9500	8180	088°	088°	088°
	← 4.3 NM	← 3.7 NM	← 5.5 NM	← 4.1 NM	← 2.1 NM	← 3.4 NM		
CATEGORY	A	B	C	D				
LPV DA*		6651/40	220 (200-¾)					
LPV DA		7445-4	1014 (1000-4)					
LNAV/VNAV DA		7327-4	896 (900-4)					
LNAV MDA	7540/55 1109 (1100-1)	7540-1¼ 1109 (1100-1¼)	7540-3 1109 (1100-3)					
CIRCLING	7540-1¼ 1089 (1100-1¼)	7540-1½ 1089 (1100-1½)	7560-3 1109 (1200-3)					NA

NW-1, 19 FEB 2026 to 19 MAR 2026

NW-1, 19 FEB 2026 to 19 MAR 2026