BUFTT ONE DEPARTURE (RNAV)

KEY WEST INTL (EYW)
KEY WEST, FLORIDA

NAVY KEY WEST DEP CON ★
124.025 313.7
ATIS
119.675
CLNC DEL
121.9
GND CON
121.9
KEY WEST TOWER ★
118.2 (CTAF) 257.8

RNAV 1-DME/DME/IRU or GPS.
RADAR required. RADAR required for non-GPS equipped aircraft.

TOP ALTITUDE: ASSIGNED BY ATC

NOTE: Jet aircraft only.

TAKEOFF MINIMUMS
Rwys 9, 27: Standard with minmum climb of 500′ per NM to 503.

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 9: Climb on heading 093° to 503, then left turn direct MOODI at or above 3000 at or below 250K, thence...

TAKEOFF RUNWAY 27: Climb on heading 273° to 503, then right turn direct SKARR, then on track 051° to cross MOODI at or above 3000 and at or below 250K, thence...

. . . on track 051° to BUFTT, then on assigned transition, maintain ATC assigned altitude, expect clearance to filed altitude within 10 minutes after departure.

GUFFS TRANSITION (BUFTT1.GUFFS)
JAYMC TRANSITION (BUFTT1.JAYMC)
MATLK TRANSITION (BUFTT1.MATLK)





CAUTION: Unmarked tethered ballon to cable within R-2916 up to 14,000 MSL.

NOTE: Chart not to scale.

SE-3, 19 FEB 2026 to 19 MAR 2026

SE-3, 19 FEB 2026 to 19 MAR 2026