

WAAS CH 72605 W32A	APP CRS 319°	Rwy Ldg 7510 TDZE 27 Apt Elev 30
--	------------------------	---

RNAV (GPS) RWY 32
SARASOTA/BRADENTON INTL (SRQ)

RNP APCH.


▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 43°C. When control tower closed, LPV and LNAV/VNAV NA; increase LNAV all Cats visibility to 1 mile. When control tower closed, inop table does not apply to LNAV Cats A and B. When control tower closed, for inop MALSR, increase LNAV Cat C and D visibility to 1½ mile.

MALS®




MISSED APPROACH: Climb to 3000 direct ACIPU and on track 047° to PAIRS and hold, continue climb-in-hold to 3000.

ATIS 124.375	TAMPA APP CON 119.65 353.575	SARASOTA TOWER ★ 120.1 (CTAF) 256.8	GND CON 121.9 273.6	CLNC DEL 118.25	UNICOM 122.95
-----------------	---------------------------------	--	------------------------	--------------------	------------------



ELEV	30	D	TDZE	27
------	----	----------	------	----



REIL Rwy 22 **L**
HIRL Rwys 14-32 and 4-22 **L**

3000 ↑	ACIPU ✦	fr 047°	PAIRS △				
*LNAV only.							
CATEGORY	A	B	C	D			
LPV DA	227-1/2		200 (200-1/2)				
LNAV/ VNAV	463-1		436 (500-1)				
LNAV MDA	440-1/2 413 (500-1/2)		440-3/4 413 (500-3/4)				
CIRCLING	500-1 470 (500-1)		600-1 1/2 570 (600-1 1/2)		600-2 570 (600-2)		