

LOC/DME I-LHI 110.1 Chan 38	APP CRS 096°	Rwy Ldg TDZE Apt Elev 8424 7 65
---	------------------------	---

ILS or LOC RWY 10L

FORT LAUDERDALE/HOLLYWOOD INTL (FLL)


DME or RADAR required.

Simultaneous approach authorized.
For inop ALS, increase S-LOC 10L Cats A, B visibility to RVR 5500.
PAKEE Fix Minimums: increase S-LOC 10L Cats A/B visibility to RVR 5500, Cats C/D to RVR 6000.

MALSRL
AS

MISSED APPROACH: Climb to 800 then climbing left turn to 4000 on FLL VOR/DME R-090 to MARTS INT/FLL 9.2 DME and hold. Continue climb-in-hold to 4000.

D-ATIS 135.0	MIAMI APP CON 133.775 285.6	FORT LAUDERDALE TOWER 119.3 257.8	GND CON 121.4
------------------------	---------------------------------------	---	-------------------------



VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 66).

One Minute Holding Pattern

HOLD I-LHI [20.8]

800 4000


MARTS INT

5000 ← 276° → 096° → 096° → 4000

GS 3.00° TCH 49

6.9 NM 3.1 NM 3.8 NM 3.9 NM 1.6 NM

ELEV 65 TDZE 7



CATEGORY	A	B	C	D	
S-ILS 10L	207/24 200 (200-½)				
S-LOC 10L	560/24	553 (500-½)	560/60	553 (500-1¼)	
CIRCLING	680-1	615 (700-1)	735 (800-2)	735 (800-2¼)	
PAKEE FIX MINIMUMS (DME REQUIRED)					
S-LOC 10L	420/24	413 (400-½)	420/40	413 (400-¾)	
CIRCLING	680-1	615 (700-1)	735 (800-2)	735 (800-2¼)	
HIRL Rwy 10L-28R and 10R-28L					
FAF to MAP 5.5 NM					
Knots	60	90	120	150	180
Min:Sec	5:30	3:40	2:45	2:12	1:50

SE-3, 19 FEB 2026 to 19 MAR 2026

SE-3, 19 FEB 2026 to 19 MAR 2026