

VORTAC CVA	APP CRS	Rwy Ldg	4001
113.8	216°	TDZE	750
Chan 85		Apt Elev	751

VOR RWY 21

DAVENPORT MUNI (DVN)



▼

▲

Rwy 21 helicopter visibility reduction below 1 SM NA. When local altimeter setting not received, use MLI altimeter setting and increase all MDAs 60 feet and S-21 visibility Cat C/D ¼ SM, and Circling visibility Cat C/D ¼ SM.

MISSED APPROACH: Climbing right turn to 2400 direct CVA VORTAC and hold.

ASOS 120.175	QUAD CITY APP CON* 125.95 257.8	CLNC DEL 118.35	UNICOM 123.0 (CTAF) 0
------------------------	---	---------------------------	---------------------------------



2400

CVA

CVA

VORTAC

2700

Remain within 10 NM

2400

CVA

7.1

HUSBO

CVA

4

1260*

3.1 NM

4 NM

*1320 when using MLI altimeter setting.

CATEGORY	A	B	C	D
S-21	1260-1 510 (600-1)		1260-1⅓ 510 (600-1⅓)	
CIRCLING	1300-1 549 (600-1)		1300-1½ 549 (600-1½)	1320-2 569 (600-2)
HUSBO FIX MINIMUMS (DME REQUIRED)				
S-21	1200-1 450 (500-1)		1200-1⅓ 450 (500-1⅓)	
CIRCLING	1300-1 549 (600-1)		1300-1½ 549 (600-1½)	1320-2 569 (600-2)