


WAAS CH 58141 W23A	APP CRS 230°	Rwy Idg 5501 TDZE 182 Apt Elev 182
--	------------------------	---

RNAV (GPS) RWY 23

SUMTER (SMS)

RNP APCH. ⚠ Circling NA to Rws 14 and 32. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -1.5°C or above 54°C. Inop table does not apply to LPV all Cats. For inop ALS increase LNAV/VNAV Cat A/B visibility to ¾ SM.	ODALS ⬆ ⬆ ⬆	MISSED APPROACH: Climb to 600 then climbing left turn to 2400 direct GAUGH and hold.
---	--	---

AWOS-3 118.075	SHAW APP CON★ 125.4	UNICOM 122.7 (CTAF) 0
--------------------------	-------------------------------	---------------------------------



MRL Rwy 5-23
REIL Rws 5 and 23

CATEGORY		A	B	C	D
LPV	DA	382-¾		200 (200-¾)	
LNAV/VNAV	DA	460-¾		278 (300-¾)	
LNAV	MDA	540-¾ 358 (400-¾)		540-7/8 358 (400-7/8)	
CIRCLING		600-1	680-1	1000-2½	1000-2¾
		418 (500-1)	498 (500-1)	818 (900-2½)	818 (900-2¾)