

WAAS CH 86936 W14A	APP CRS 141°	Rwy Ldg 5600 TDZE 953 Apt Elev 953
--	------------------------	---


RNAV (GPS) RWY 14

NEWTON MUNI-EARL JOHNSON FLD (TNU)


⚠ DME/DME RNP-0.3 NA. When local altimeter setting not received use Des Moines altimeter setting and increase all DA/MDA 80 feet; increase LPV and LNAV/VNAV all Cats and LNAV Cats C/D and Circling Cat C/D visibility ¼ mile. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -13°C (9°F) or above 54°C (130°F). Rwy 14 helicopter visibility reduction below ¾ SM NA. Baro-VNAV and VDP NA when using Des Moines altimeter setting.

MISSED APPROACH: Climb to 2700 direct UBHIT and hold.

AWOS-3 132.275	DES MOINES APP CON 123.9 307.15	CLNC DEL 126.3	UNICOM 122.8 (CTAF) 0
--------------------------	---	--------------------------	---------------------------------



ELEV 953	TDZE 953
-----------------	-----------------



REIL Rwy 14 **0**
MIRL Rwy 14-32 **0**

4 NM Holding Pattern 3100 ← 321° GP 3.00° TCH 39	KOWDO		EBSUH	2700	UBHIT
	6 NM 3100 ← 321° → 2600		2600 141° * 1.3 NM to RWY14	2600 141° * LNAV only.	RWY14 1.3 NM
CATEGORY	A	B	C	D	
LPV DA	1203-7/8		250 (300-7/8)		
LNAV/VNAV DA	1203-7/8		250 (300-7/8)		
LNAV MDA	1420-1 467 (500-1)		1420-1 3/8 467 (500-1 3/8)		
CIRCLING	1420-1 467 (500-1)	1440-1 1/2 487 (500-1 1/2)	1520-1 1/2 567 (600-1 1/2)	1600-2 647 (700-2)	

NEWTON, IOWA
Amdt 1B 21JUN18

NEWTON MUNI-EARL JOHNSON FLD (TNU)
41°40'N-93°01'W
RNAV (GPS) RWY 14

NC-3, 19 FEB 2026 to 19 MAR 2026

NC-3, 19 FEB 2026 to 19 MAR 2026