

WAAS CH <b>42726</b> <b>W23A</b>	APP CRS <b>234°</b>	Rwy Ldg TDZE <b>443</b> Apt Elev <b>459</b>	<b>5722</b>
--	------------------------	---	-------------

# RNAV (GPS) RWY 23

MOORE COUNTY (SOP)

RNP APCH.


▼ Baro-VNAV NA when using Sanford altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. When local altimeter setting not received, use Sanford altimeter setting and increase all DA 88 feet and all MDA 100 feet; increase LNAV Cats C/D visibility 3/8 mile and Circling Cat C visibility 1/2 mile. Rwy 23 helicopter visibility reduction below 3/4 SM NA.

MISSED APPROACH:  
Climb to 2500 direct  
HEBNO and hold.



AWOS-3PT  
**127.575**

FAYETTEVILLE APP CON  
**127.8 343.725**

UNICOM  
**123.05(CTAF) 0**



ELEV <b>459</b>	<b>D</b>	TDZE <b>443</b>
-----------------	----------	-----------------



CATEGORY	A	B	C	D
LPV DA		693-1	250 (300-1)	
LNAV/VNAV DA		699-1	256 (300-1)	
LNAV MDA		780-1	337 (400-1)	
CIRCLING	880-1 421 (500-1)	920-1 461 (500-1)	1100-1 3/4 641 (700-1 3/4)	1360-3 901 (1000-3)

SE-2, 19 FEB 2026 to 19 MAR 2026

SE-2, 19 FEB 2026 to 19 MAR 2026