

WAAS CH <b>86606</b> <b>W36B</b>	APP CRS <b>005°</b>	Rwy Ldg TDZE <b>595</b> Apt Elev <b>629</b>
--	------------------------	---

# RNAV (GPS) RWY 36R

HUNTSVILLE INTL-CARL T JONES FLD (HSV)




RNP APCH - GPS.

**ASR** Circling NA for Cats C/D/E east of Rwy 18L-36R. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -9°C or above 54°C. Simultaneous approach authorized. LNAV procedure NA during simultaneous operations. Use of FD or AP required during simultaneous operations. For inop ALS increase LPV Cat E visibility to RVR 4000, LNAV/VNAV Cat E visibility to RVR 5000 and LNAV Cat E visibility to RVR 6000.

MALSRL


MISSED APPROACH: Climb to 3000 direct BISBE and hold.

ATIS <b>121.25</b>	HUNTSVILLE APP CON * <b>125.6 354.1</b>	HUNTSVILLE TOWER * <b>127.6 (CTAF) 0 350.35</b>	GND CON <b>121.9 269.525</b>	CLNC DEL <b>120.35</b>	UNICOM <b>122.95</b>
-----------------------	--	--	---------------------------------	---------------------------	-------------------------



ELEV 629	<b>D</b> TDZE 595
----------	-------------------

TDZ/CL Rws 18R and 36L  
HIRL Rws 18L-36R and 18R-36L



LPV DA	818/24		223 (200-1/2)	
LNAV/DA	939/30		344 (400-5/8)	
LNAV MDA	980/24	385 (400-1/2)	980/35	385 (400-5/8)
CIRCLING	1160-1	531 (600-1)	1160-1 1/2 531 (600-1 1/2)	1240-2 611 (700-2)
				1260-2 1/4 631 (700-2 1/4)

SE-4, 19 FEB 2026 to 19 MAR 2026

SE-4, 19 FEB 2026 to 19 MAR 2026