

WAAS CH 62824 W28A	APP CRS 282°	Rwy Idg TDZE Apt Elev	5060 969 974
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 28


POLK COUNTY/CORNELIUS MOORE FLD (4A4)

RNP APCH.


NA Baro-VNAV and VDP NA when using Cartersville altimeter setting. Rwy 28 helicopter visibility reduction below $\frac{3}{4}$ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -8°C or above 54°C. Obtain local altimeter setting on CTAF, when not received, use Cartersville altimeter setting: increase LPV DA to 1287 feet; increase LNAV/VNAV DA to 1353 feet and all visibility $\frac{1}{8}$ SM; increase all MDAs 80 feet and visibility Cats C and D $\frac{1}{8}$ SM.

MISSED APPROACH: Climb to 1500 then climbing left turn to 3100 direct GUSSY and hold.

ATLANTA CENTER 124.5 270.325	UNICOM 122.8 (CTAF)
--	-------------------------------



ELEV 974	TDZE 969
MIRL Rwy 10-28	



	1 NM	1.4 NM	2.7 NM	6.6 NM	
CATEGORY	A	B	C	D	
LPV DA		1219-1	250 (300-1)		
LNAV/VNAV DA		1285-1	316 (400-1)		
LNAV MDA		1300-1	331 (400-1)		

SE-4, 19 FEB 2026 to 19 MAR 2026

SE-4, 19 FEB 2026 to 19 MAR 2026