ILS Y or LOC Y RWY 28
STATESVILLE RGNL (SVH)

LOC/DME I-SVH	APP CRS	Rwy ldg	6453
111.75	285°	TDZE	967
Chan 54 (Y)		Apt Elev	968

DME required.

When local altimeter setting not received, use Lincolnton altimeter setting and increase ILS DA to 1219 and all MDA 60 feet; increase S-LOC 28 Cats C/D visibility ⅛ mile and Circling Cat C visibility ¼ mile. VDP NA when using Lincolnton altimeter setting. For inop MALSR when using Lincolnton altimeter setting, increase S-ILS 28 all Cats visibility to ⅞ mile and S-LOC 28 Cats C/D visibility to 1 mile.

MALSR

MISSED APPROACH: Climb to 1700 then climbing left turn to 3400 on heading 105° and on CLT VOR/DME R-025 to PEGTE INT/I-SVH 13.2 DME and hold.

AWOS-3	ATLANTA CENTER	UNICOM
119.225	125.15 263.0	123.075 (CTAF) L





REIL Rwy 10 L
HIRL Rwy 10-28 L

CATEGORY	A	B	C	D
S-ILS 28	1167-½ 200 (200-½)			
S-LOC 28	1280-½ 313 (400-½)			
C CIRCLING	1420-1 452 (500-1)	1540-1 572 (600-1)	1540-1½ 572 (600-1½)	1560-2 592 (600-2)

SE-2, 19 FEB 2026 to 19 MAR 2026