

WAAS CH 93735 W02A	APP CRS 018°	Rwy Idg TDZE Apt Elev	5000 262 262
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 2

KENNETT MEML (TKX)

⚠

NA

Circling to Rwy 18/36 NA at night. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F). Circling NA west of Rws 2 and 18.
DME/DME RNP-0.3 NA. When local altimeter setting not received, use Blytheville altimeter setting and increase all DA 47 feet and all MDA 60 feet; increase LNAV/VNAV visibility all Cats and LNAV Cats C/D visibility ½ mile; increase Circling Cat D visibility ¼ mile. Helicopter visibility reduction below 1 SM NA. Rwy 2 Straight-in and Circling minimums NA at night.

MISSED APPROACH:
Climb to 2500 direct
OGVIE and hold.

AWOS-3PT 119.05	MEMPHIS CENTER 120.075 289.4	UNICOM 122.8 (CTAF) 0
---------------------------	--	---------------------------------

⚠ 862

MISSED APCH FIX

ELEV 262		TDZE 262	
4 NM Holding Pattern		2500 OGVIE *LNAV only.	
GP 3.00° TCH 40		2500 018° 018° 1900 1900 018° 2 6.1 NM 3 NM 2 NM	
CATEGORY	A	B	C
LPV DA	512-1 250 (300-1)		
LNAV/VNAV DA	538-1 276 (300-1)		
LNAV MDA	620-1 358 (400-1)		
CIRCLING	660-1 398 (400-1)	720-1 458 (500-1)	720-1½ 458 (500-1½)

81

20

36

3012 X 75

5000 X 75

2

018° to RW02

REIL Rws 2 and 20

MIRL Rws 2-20 and 18-36

KENNETT, MISSOURI

Amtd 1A 28APR16

36°14'N-90°02'W

KENNETT MEML (TKX)

RNAV (GPS) RWY 2