

WAAS CH 86805 W36A	APP CRS 005°	Rwy ldg TDZE 417 Apt Elev 418
--	------------------------	---

RNAV (GPS) RWY 36

PERRY-HOUSTON COUNTY (PXE)

RNP APCH-GPS.

Baro-VNAV and VDP NA when using Middle Georgia Rgnl altimeter setting. Rwy 36 helicopter visibility reduction below ¾ SM NA. Inop table does not apply to LPV and LNAV/VNAV all Cats. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. When local altimeter setting not received, use Middle Georgia Rgnl altimeter setting and increase LPV DA and LNAV/VNAV DA to 705 feet; increase all MDAs 40 feet; and Circling visibility Cat C/D ¼ SM. For inop ALS, increase LNAV Cats A/B visibility to 1 SM and Cat C/D to 1 ¾ SM. For inop ALS, when using Middle Georgia Rgnl altimeter setting; increase LPV and LNAV/VNAV all Cats visibility to ¾ SM and LNAV Cat A/B visibility to 1 SM.

MALSRL

MISSED APPROACH:

Climb to 2300 direct ANICU and hold.

AWOS-3 123.825	ATLANTA APP CON ★ 124.2 279.6	UNICOM 122.725 (CTAF) 0
--------------------------	---	-----------------------------------

MISSED APCH FIX

4 NM

185°

005°

ANICU

Δ 980

Δ 837

Δ 608

Δ 755±

Δ 863

Δ 637

Δ 443

Δ 2100

RW36

(FAF) PRDUE

(IF/IAF) SCTRY

HOLD 4000 2300

005°

185°

4 NM

30 NM to SCTRY

2600

15 NM to SCTRY

2300

SCTRY

095°

275°

30 NM to SCTRY (NoPT)

2300

095°

275°

ELEV 418	TDZE 417
-----------------	-----------------

8 L

5000 X 100

36

005°

HIRL Rwy 18-36 0

2300 ANICU

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 30).

PRDUE

SCTRY

4 NM Holding Pattern

185°

005°

4000

2300

GP 3.00°

TCH 45

1.4 NM to RW36

2100

2100

1.4

3.7 NM

6.7 NM

CATEGORY	A	B	C	D
LPV DA	667-¾ 250 (300-¾)			
LNAV/VNAV DA	667-¾ 250 (300-¾)			
LNAV MDA	900-¾	483 (500-¾)	900-1	483 (500-1)
CIRCLING	900-1	482 (500-1)	1140-2 722 (800-2)	1280-2¾ 862 (900-2¾)

PERRY, GEORGIA
Amdt 2 08SEP22

32°31'N-83°46'W

PERRY-HOUSTON COUNTY (PXE)

RNAV (GPS) RWY 36

SE-4, 19 FEB 2026 to 19 MAR 2026

SE-4, 19 FEB 2026 to 19 MAR 2026