


WAAS CH 42505 W31A	APP CRS 314°	Rwy Ldg TDZE Apt Elev	6500 487 501
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 31

LANCASTER RGNL (LNC)

<p>⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 47°C (116°F). DME/DME RNP-0.3 NA. Baro-VNAV NA when using Dallas Exec altimeter setting. When local altimeter setting not received, use Dallas Exec altimeter setting and increase LPV DA to 732 feet; increase LNAV/VNAV DA to 970 feet and visibility all Cats ¼ SM; increase all MDAs 60 feet and LNAV Cats C/D and Circling Cats C/D visibility ¼ SM.</p>		<p>MISSED APPROACH: Climb to 2000 direct DOCAV and right turn on track 053° to WARER then climb to 3000 on track 053° to SOLDO and hold.</p>
AWOS-3PT 118.975	LONE STAR APP CON 125.2 343.65	UNICOM 122.7 (CTAF) 0



ELEV 501	TDZE 487
----------	----------

	2000 DOCAV	WARER	3000 SOLDO	VIYUN
	tr 053°	tr 053°		
* LNAV only	OTAZY 1.5 NM to RW31	JUTON		
	RW31	1800	2700	
	1.5 NM	2.5 NM	6 NM	
		1000*	1800	GP 3.00° TCH 50
CATEGORY	A	B	C	D
LPV DA		687-¾	200 (200-¾)	
LNAV/VNAV DA		925-1½	438 (500-1½)	
LNAV MDA		880-1	393 (400-1)	880-1¼ 393 (400-1¼)
CIRCLING	980-1 479 (500-1)	1020-1 519 (600-1)	1300-2¼ 799 (800-2¼)	1300-2½ 799 (800-2½)

SC-2, 19 FEB 2026 to 19 MAR 2026

SC-2, 19 FEB 2026 to 19 MAR 2026