

WAAS
CH **49229**
W29A

APP CRS
291°

Rwy Idg
TDZE **1989**
Apt Elev **1989**

RNAV (GPS) RWY 29

L M CLAYTON (OLF)

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C (0°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Wokal FLD/Glasgow-Valley County altimeter setting: increase LPV DA to 2330 ft and visibility ¾ SM, LNAV/VNAV DA to 2380 ft and visibility ½ SM; increase all MDA 160 feet and LNAV and Circling visibility Cat C/D ½ SM. Baro-VNAV and VDP NA with Glasgow altimeter setting.

MISSED APPROACH:

Climb to 4500 direct
RULIE and hold.

ASOS 118.325	SALT LAKE CENTER 126.85 305.2	UNICOM 122.8 (CTAF) 0
------------------------	---	---------------------------------

ELEV **1989**

TDZE **1989**

4500

RULIE

*LNAV only.

GETKE
2.9 NM to
RW29

1 NM

1.9 NM

3 NM

6 NM

CATEGORY

LPV DA

LNAV/VNAV DA

LNAV MDA

CIRCLING

VGSI and RNAV glidepath not coincident
(VGSI Angle 3.00°/TCH 29).

3900

2940*

3900

291°

111°

4800

GP 3.00°
TCH 40

A

B

C

D

2189-¾

200 (200-¾)

2239-⅞

250 (300-⅞)

2340-1

351 (400-1)

2480-1

491 (500-1)

2660-2
671 (700-2)

2780-2½
791 (800-2½)

MIRL Rwy 11-29 0

REIL Rwy 11-29 0

5091 X 100

291° to
RW29

WOLF POINT, MONTANA

Amcl 1B 14JUL22

48°06'N-105°35'W

L M CLAYTON (OLF)

RNAV (GPS) RWY 29