

WAAS CH <b>69628</b> <b>W28A</b>	APP CRS <b>280°</b>	Rwy Ldg TDZE Apt Elev	<b>5003</b> <b>868</b> <b>868</b>
--	------------------------	-----------------------------	---

# RNAV (GPS) RWY 28




FAIRFIELD COUNTY (L.H.Q.)

RNP APCH - GPS.

**⚠** Rwy 28 helicopter visibility reduction below 1 SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -20°C or above 54°C. Baro-VNAV NA when using Rickenbacker Intl altimeter setting. When local altimeter setting not received, use Rickenbacker Intl altimeter setting; increase LPV DA to 1411 feet and all visibilities ¼ SM; increase LNAV/VNAV DA to 1549 feet and all visibilities ¼ SM; increase all MDAs 60 feet. Straight-in Rwy 28 at night, operational VGSI required, remain on or above VGSI glidepath until threshold. When Circling Rwy 28 at night, operational VGSI required, remain on or above VGSI glidepath until threshold.


**MISSED APPROACH:**  
Climb to 2700 direct HASPI and hold.

ASOS <b>118.375</b>	COLUMBUS APP CON <b>134.0 279.6</b>	CLNC DEL <b>121.65</b>	UNICOM <b>122.725 (CTAF) 0</b>
------------------------	--	---------------------------	-----------------------------------



ELEV	868	TDZE	868
------	-----	------	-----

CATEGORY		A	B	C	D
LPV DA		1362-1⅜	494 (500-1⅜)		NA
LNAV/VNAV DA		1500-1¾	632 (700-1¾)		NA
LNAV MDA		1500-1	632 (700-1)		NA
CIRCLING		1500-1 632 (700-1)	1540-1 672 (700-1)		NA



REIL Rwy 10 and 28 0  
MIRL Rwy 10-28 0

EC-2, 19 FEB 2026 to 19 MAR 2026

EC-2, 19 FEB 2026 to 19 MAR 2026