

VORTAC FBC
108.2
Chan 19

APP CRS
104°

Rwy Idg
TDZE
Apt Elev
N/A
N/A
830

VOR-A

WYANDOT COUNTY (56D)


Procedure NA at night. When local altimeter setting not received, use Marion altimeter setting: increase all MDAs 40 feet and visibility Cat C/D ¼ SM.

MISSED APPROACH: Climbing left turn to 2500 on FBC VORTAC R-104 to RITRO INT/15 DME and hold.

FDY ASOS
132.85

CLEVELAND APP CON ★
128.35 360.65

UNICOM
123.05 (CTAF) 0



ADF or DME REQUIRED

ELEV 830

One Minute Holding Pattern

2500 ← 284°
104° →

FBC VORTAC

RITRO INT
FBC 15

YEVUN
FBC 18

MADDA
FBC 20.5

1520

104°

2500

15 NM

3 NM

2.5

2500
FBC R-104

RITRO INT

104°

3997 X 75

36

CATEGORY	A	B	C	D
CIRCLING	1520-1 690 (700-1)	1520-1¼ 690 (700-1¼)	1540-2 710 (800-2)	1540-2¼ 710 (800-2¼)
YEVUN FIX MINIMUMS (DME REQUIRED)				
CIRCLING	1420-1 590 (600-1)	1440-1 610 (700-1)	1540-2 710 (800-2)	1540-2¼ 710 (800-2¼)

LRL Rwy 18-36 0

FAF to MAP 5.5 NM

Knots	60	90	120	150	180
Min:Sec	5:30	3:40	2:45	2:12	1:50