

WAAS
CH **93515**
W36A

APP CRS
002°

Rwy ldg **3513**
TDZE **73**
Apt Elev **74**

RNAV (GPS) RWY 36

HOLK FLD AT FOLEY MUNI (5R4)

RNP APCH - GPS

NA

Procedure NA at night. Rwy 36 helicopter visibility reduction below 1 SM NA. Use Fairhope altimeter setting. When not received, use Gulf Shores altimeter setting and increase all MDA 20 feet; increase LP and LNAV Cat C visibility 1/8 SM and Circling Cat C visibility 1/4 SM.

MISSED APPROACH:

Climb to 3100 direct RUPQE and hold, continue climb-in-hold to 3100.

CQF AWOS-3PT
118.425

PENSACOLA APP CON
118.6 380.6

UNICOM
123.05 (CTAF) 0

The chart displays the RNAV (GPS) RWY 36 approach. Key features include:

- Initial Approach:** A 4 NM climb from 3000 to 3100 feet, then a 182° turn to 002°.
- Waypoints:** HEKAL (2.5 NM to RW36), AWAGE (FAF), and WBIK (IF/IAF).
- Altitudes:** 3100, 3000, 1500, 900, and 36 feet.
- Distances:** 4 NM, 2.5 NM, 1.9 NM, and 6.1 NM.
- Obstacles:** 494, 349, 298, 190±, 177±, and 292.
- Navigation:** 092° and 272° headings, 002° and 182° turns.

ELEV 74

TDZE 73

3100 RUPQE

AWAGE

HEKAL 2.5 NM to RW36

WBIK 4 NM Holding Pattern

1500

900

36

3700 X 74

0.3% UP

002°

CATEGORY	A	B	C	D
LP MDA	500-1 427 (500-1)		500-1¼ 427 (500-1¼)	NA
LNAV MDA	500-1 427 (500-1)		500-1¼ 427 (500-1¼)	NA
CIRCLING	680-1 606 (700-1)		880-2¼ 806 (900-2¼)	NA

Foley, Alabama

Amdt 2A 30NOV23

30°26'N-87°42'W

HOLK FLD AT FOLEY MUNI (5R4)

RNAV (GPS) RWY 36