

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Inop table does not apply.

ALSF-2

MISSED APPROACH: Climb to 800, then climbing left turn to 2500 direct EARTH and hold.

ORLANDO APP CON 134.95 281.425	NASA TOWER ★ 128.55 (CTAF) 284.0	GND CON 121.75
-----------------------------------	-------------------------------------	-------------------

RADAR REQUIRED

Approach Path:
ROCIT (IF) → STARS (FAF) → RW15
Altitudes: 2500, 1500, 1500, 105 ± 10, 508, 582, 397
Distances: 9 NM, 2500 (6), 1500 (6), 105 ± 10, 508, 582, 397
Obstacles: 508, 582, 397
CAPE CANAVERAL SFS SKID STRIP

Missed Approach:
Climb to 800, then climbing left turn to 2500 direct EARTH and hold.

ROCIT	2500	155°	1500	STARS	1500	155°	1000	RW15
GP 3.00° TCH 55								
	6.1 NM		3.6 NM		0.9 NM			
CATEGORY	A	B	C	D	E			
LPV DA		208-1	200 (200-1)					
LNAV/VNAV DA		286-1	278 (300-1)					
LNAV MDA		360-1	352 (400-1)					
CIRCLING	420-1 411 (500-1)	460-1 451 (500-1)	940-2 3/4 931 (1000-2 3/4)	940-3	931 (1000-3)			

Missed Approach:
Climb to 800, then climbing left turn to 2500 direct EARTH and hold.

Obstacles: 107, 33
Distance: 1.5001 x 300

TITUSVILLE, FLORIDA
Amdt 1A 25MAY17

SPACE FLORIDA LAUNCH AND LANDING FACILITY (TTS)
28°37'N-80°42'W

RNAV (GPS) RWY 15