

WAAS CH 81830 W17A	APP CRS 173°	Rwy Ldg 12000 TDZE 5339 Apt Elev 5434
--	------------------------	--

RNAV (GPS) Y RWY 17L

DENVER INTL (DEN)

▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -25°C (-13°F) or above 48°C (119°F). DME/DME RNP-0.3 NA. LNAV procedure NA during simultaneous operations. For inoperative MALS R increase LNAV Cats C/D visibility to RVR 5500. Use of FD or AP providing RNAV track guidance required during simultaneous operations. Simultaneous approach authorized with Rwy 16L/16R and 17R.
RVR 1800 authorized with use of FD or AP or HUD to DA.

MALS R


MISSED APPROACH:
Climb to 5900 then climbing left turn to 10000 direct LIMEX and hold.





D-ATIS
125.6 379.9

DENVER APP CON
119.3 307.3 (N)
120.35 379.3 (S)

DENVER TOWER
132.35 239.275

GND CON
121.35 379.175 (W)
121.85 377.1 (E)

RADAR REQUIRED



CATEGORY	A	B	C	D
LPV DA#	5539/24 200 (200-½)			
LNAV/VNAV DA	5648/24 309 (300-½)			
LNAV MDA	5700/24 361 (300-½)		5700/35 361 (300-⅝)	

SW-1, 19 FEB 2026 to 19 MAR 2026

SW-1, 19 FEB 2026 to 19 MAR 2026